



**DS-2AM1-612X/602X Analog Speed Dome
Technical Manual**

Notices

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2010 by HIKVISION. All rights reserved.

This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied. It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

This documentation is provided "as-is," without warranty of any kind.

Please send any comments regarding the documentation to:
overseabusiness@hikvision.com

Find out more about HIKVISION at www.hikvision.com

Contents

1. Key Features
2. Specifications
3. Dimension

1. Key Features

- High Performance Sony CCD
- 75°/s Pan Preset Speed and 50°/s Tilt Preset Speed
- 0.2-75°/s Manual Pan Speed and 0.3-50°/s Manual Tilt Speed
- Park Action: Start to Call Preset / Patrol / Auto Scan, after a Defined Time of Inactivity
- Parameter Restore: PTZ & Lens Status after Reboot
- Proportional Pan / Tilt: Continually Decreases Pan / Tilt Speeds, in Proportion to Depth of Zoom
- Programmable Limit Stops for Auto Scan
- Built-in Surge Protection and Limited Lightning Protection
- Water and Dust Resistance: IP66, for Outdoor Dome
- Working Temperature -30°C ~ 60°C (Outdoor Models) or -10°C ~50°C (Indoor Models)

2. Specifications

Parameter		DS-2AM1-612X DS-2AM1-602X
Camera	Image Sensor	1/4 inch Sony Super HAD CCD
	Effective Pixels	PAL: 752 (H)×582 (V) NTSC: 768 (H)×494 (V)
	Horizontal Resolution	480TVL
	Signal System	NTSC / PAL
	Min. Illumination	0.1Lux/F1.6
	White Balance	Auto / ATW / Indoor / Outdoor
	AGC	Auto / Manual
	S/N Ratio	Better than 50dB
	BLC	ON / OFF
	Electronic Shutter	N: 1/60~1/10,000s (16 steps), P: 1/50~1/10,000s (16 steps)
	Day & Night	Electronic
	Digital Zoom	---
	Auto Focus	Auto / Manual
Lens	Focal Length	3.9-85.8mm, 22x zoom
	Zoom Speed	Approx. 3.7sec (Optical WIDE-TELE)
	Angular of View	51.2 degree (WIDE end) to 4.2 degree (TELE end)
	Min. Working Distance	100mm (WIDE end), 1000mm (TELE end)
	Aperture Range	F1.6-F3.7
Pan and Tilt	Pan Range	360° endless
	Pan Speed	Manual: approx. 0.2°/s-75°/s Preset: up to approx. 75°/s
	Tilt Range	0°~90°
	Tilt Speed	Manual: approx. 0.2°- 50°/s

		Preset: up to approx. 50°/s
	Proportional Pan/Tilt Control	YES
	Number of Presets	104
	Auto Mode	OFF / Preset 1-3 / Patrol 1 / Auto Scan 1
	Patrol	.1 / 2 / 3
	Parameter Restore	Go to the speed dome last status after reboot
	Park Action	Trigger Action: Preset / Patrol / Auto Scan, after a defined time of inactivity
Monitor Output	Monitor Output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
General	RS-485 Protocols	HIKVISION, PELCO-P, PELCO-D (addible), self-adaptive
	Power Supply	24VAC (12VDC option)
	Power Consumption	12W (50W Heater ON, Except indoor dome)
	Working Temperature / Humidity	.-30°C ~ 60°C (outdoor) / -10°C ~ 50°C (indoor) 90% or less (without condensation)
	Water and Dust Resistance	IP66 standard compatible (Just for Outdoor dome), TVS 3000V limited lightning protection
	Dimensions	6 inch, Φ243 (mm)×287 (mm)
	Weight (approx.)	5kg

3. Dimension

