



**DS-2DM1-614X/604X IP Speed Dome
Technical Manual**

Notices

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2010 by HIKVISION. All rights reserved.

This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied. It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

This documentation is provided "as-is," without warranty of any kind.

Please send any comments regarding the documentation to:
overseabusiness@hikvision.com

Find out more about HIKVISION at www.hikvision.com

Contents

1. Key Features
2. Specifications
3. Dimension

1. Key Features

- High Performance Sony CCD
- 20°/s Pan Preset Speed and 15°/s Tilt Preset Sp0EED
- 0.3-20°/s Manual Pan Speed and 0.85-15°/s Manual Tilt Speed
- Park Action: Start to Call Preset / Patrol / Auto Scan, after a Defined Time of Inactivity
- Parameter Restore: PTZ & Lens Status after Reboot
- Proportional Pan / Tilt: Continually Decreases Pan / Tilt Speeds, in Proportion to Depth of Zoom
- Programmable Limit Stops for Auto Scan / Manual Models
- Programmable Zoom Speeds
- Built-in Menu System for Setup of Programmable Functions
- On-Screen Compass, Pan, Tilt and Zoom Display
- Support Mouse Drag and Zoom
- Alarm I/O: 1 Channel Input and 1 Channel Relay Output
- Alarm Actions: 200 Presets, 8 Patrols, 4 Patterns, Auto Scan, Alarm Output, SD Memory Recording and Notification on PC Client
- Resume after Alarm: Allow the Dome Return to Previous State after Alarm Acknowledgement
- Built-in Surge Protection and Limited Lightning Protection
- Water and Dust Resistance: IP66, for Outdoor Dome
- Working Temperature -30°C ~ 60°C (Outdoor Models) or -10°C ~50°C (Indoor Models)

2. Specifications

Parameter		DS-2DM1-614X DS-2DM1-604X
Camera	Image Sensor	1/4 Inch Sony Super HAD CCD
	Effective Pixels	PAL: 752 (H)×582 (V) NTSC: 768 (H)×494 (V)
	Horizontal Resolution	480 (Color) 520 (B/W)
	Signal System	NTSC / PAL
	Min. Illumination	0.2Lux / F1.6 (Color) 0.02Lux / F1.6 (B/W)
	White Balance	Auto / ATW / Indoor / Outdoor
	AGC	Auto / Manual
	S/N Ratio	Better than 50dB
	BLC	ON / OFF
	Shutter	N: 1/60~1/120,000s P: 1/50~1/120,000s
	Day & Night	ICR
	Privacy Blank	---
	Digital Zoom	---
	Auto Focus	Auto / Manual
Lens	Focal Length	3.84-88.4mm, 23X
	Zoom Speed	5.4s (Optical , WIDE-TELE)
	Angular of View	52.2°-2.36 ° (WIDE-TELE)
	Min. Working Distance	1200mm (TELE)
	Aperture Range	F1.6-F3.2
Pan and Tilt	Pan Range	360° endless
	Pan Speed	Manual: approx. 0.3°/s-20°/s Preset: up to approx. 20°/s
	Tilt Range	0°~90°

	Tilt Speed	Manual: approx. 0.85°~15°/s Preset: up to approx. 15°/s
	Proportional Pan / Tilt Control	YES
	Number of Presets	200
	Auto Mode	OFF / Preset / Patrol / Pattern / Auto Scan / Random Scan / Frame Scan
	Patrols	8
	Patterns	1 / 2 / 3 / 4
	Freeze Frame	Freeze Frame during Preset.
	Parameter Restore	Go to the speed dome last status after reboot
	Park Action	Trigger Action: Preset / Patrol / Auto Scan, after a defined time of inactivity
	PTZ Position Display	ON / OFF
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Image Resolution	PAL: 704×576, NTSC: 704×480
	Frame Rate	25fps (704×576), 30fps (704×480)
	Image Compression	H.264
	Audio Compression	OggVorbis / 16kbps
	Audio Mode	OFF / Audio input / Audio output
	Protocols	TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE (FTP, SMTP, NTP, SNMP addible)
	No. of Simultaneous Users	Up to 6 users
	Dual Streams	Support Dual Streams Simultaneously
	Mini SD Memory Card	Manual REC / Alarm REC. Compatible SDHC Standard Cards
	User / Host Level	3 Levels: Administrator, Camera control, Live only
	Security Measures	User authentication (ID and PW), Host authentication (MAC address)
Client GUI	Camera Control	Pan/Tilt, Zoom, Focus, Click centering, Drag zoom, Iris, Preset position call and program, Auto mode.
	Camera Title	Up to 18 characters
	Menu Language	English, Chinese
	Clock Display	Time: Week: Date, 6 formats on the Client
Alarm	Alarm Input	1 channel input
	Alarm Output	1 channel output, alarm linkage is configurable
	Alarm Actions	Preset 1 to 200, Patrol 1 to 8, Auto Scan 1 to 4, SD card recording, Terminal output, Notification on Client.
Input / Output	Monitor Output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
	Microphone Input	Mic. In (Applicable microphone; Plug-in power type)

		2-2.4V[p-p], Input impedance: 1KΩ±10%
	Audio Output	Audio out, Line level
General	Menu Language	English, Chinese
	RS-485 Protocols	HIKVISION, PELCO-P, PELCO-D (addible), self-adaptive
	Power Supply	24VAC (12VDC option)
	Power Consumption	12W (50W Heater ON, Except indoor dome)
	Working Temperature / Humidity	.-30°C ~ 60°C (outdoor) / -10°C ~ 50°C (indoor), 90% or less (without condensation)
	Water and Dust Resistance	IP66 standard compatible (Just for Outdoor dome), TVS 3000V limited lightning protection
	Dimensions	6 inch, Φ243 (mm)×287 (mm)
	Weight (approx.)	5kg

3. Dimension

