

**Medium Speed Long Range PTZ camera
DTC810LR**



Features:

- Long distance surveillance camera kits, equipped with professional zoom LENS, effective identify range above 500 meters, visible effective range above 1KM.
- Built-in Wide dynamic, high resolution camera for your surveillance without missing any details.
- Aluminum housing with temperature control, water-proof, suitable for all climates.
- Wide range heavy duty pan / tilt platform, easy control and monitor.
- Support RS485 communication and standard PELCO protocol for full control of the devices.

Specifications:

Camera	Image Sensor	1/3" SONY CCD / SS-3
	Resolution	PAL:792(H) x 698(V) / NTSC:768(H) x 494(V)
	TV Lines	Horizontal 540tvl / Vertical 460tvl
	TV Signal Type	PAL and NTSC compatible
	SNR	> 50dB
	WDR Mode	4 modes
	White Balance Mode	AUTO/PUSH/MANU/INDR/PLUO/OUTD
	OSD Control	Yes
	Illumination	Color: 0.6Lux(F1.2); Slow Shuttle: 0.08Lux(F1.2)
	Anti Color Rolling	Yes
	Video Output	1.0-1.2vpp 75Ω
LENS	Focal Length	30 ~ 300mm

	Field	15°30' ~ 1°33'
	Aperture Range	F3.5 ~ 360°
	Distance Range	10 ~ 1Km (visible)
	Zoom Control	motorized
	Focus Control	motorized
	Iris Control	motorized
Housing type	Aluminum & metal	
Housing size	585 x 185 x 175mm	
Pan Range	0 ~ 90°	
Tilt Range	0 ~ 355°	
Preset Position	128 positions	
Cursing	1 tour support 10 preset positions.	
Position Precision	< 1 degree.	
Protocol	PELCO-D/P	
Baud Rate	1200 / 2400 / 4800 / 9600	
Address	0 ~ 45	
Communicate	RS485	
Operation Temperature	-10° ~+ 50° RH95% (max)	
Power Supply	24VAC	
Power Consumption	60W (max)	
Weight	5kg	