

## Key Board DTK-202



Model	Specification	
<b>Features</b>	<p><b>LCD display.</b>  <b>Password and key access mechanism</b>  <b>With 2 axis / 3 axis for controlling matrix, high-speed dome and P.T. platform etc.</b>  <b>Suitable for controlling decoders, Zoom cameras, Splitters, Multiplexers and DVRs etc.</b>  <b>Supported up to 16 cascade keyboards working together.</b>  <b>Supported multi scale matrix and matrix array.</b>  <b>Available for controlling alarm systems, providing set alarm, arm, dis-arm functions.</b></p>	
<b>Specification</b>	<b>Power Supply</b>	<b>DC9~12V, 500mA</b>
	<b>Communication Port</b>	<b>RS485</b>
	<b>Protocols</b>	<b>PELCO-D, PELCO-P, ALEC, YAAN, SAMSUNG</b>
	<b>Baud Rate</b>	<b>9600 / 4800 / 2400 / 1200 bps/s</b>
	<b>Video SNR</b>	<b>50db</b>
	<b>Working Temperature</b>	<b>-10°C ~ 55°C</b>
	<b>Working Humidity</b>	<b>≤ 90% RH</b>
	<b>Unit Size</b>	<b>370 x 180 x 80 (mm)</b>
	<b>Unit Weight</b>	<b>&gt; 2.5kg (depending on different style)</b>